


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



B31

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G01N 21/25, 21/33, A61B 5/00		A1	(11) International Publication Number: WO 98/22805
			(43) International Publication Date: 28 May 1998 (28.05.98)
<p>(21) International Application Number: PCT/US97/20324</p> <p>(22) International Filing Date: 7 November 1997 (07.11.97)</p> <p>(30) Priority Data: 60/033,334 21 November 1996 (21.11.96) US 08/898,604 22 July 1997 (22.07.97) US</p> <p>(71) Applicant: BOSTON SCIENTIFIC CORPORATION [US/US]; One Boston Scientific Place, Natick, MA 01760-1537 (US).</p> <p>(72) Inventor: CROWLEY, Robert, J.; 64 Puritan Lane, Sudbury, MA 01776 (US).</p> <p>(74) Agent: CAPRARO, Joseph, A.; Testa, Hurwitz & Thibault, LLP, High Street Tower, 125 High Street, Boston, MA 02110 (US).</p>			<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report.</i></p>
<p>(54) Title: MINIATURE SPECTROMETER</p> <div style="text-align: center;"></div>			
<p>(57) Abstract</p> <p>A miniaturized spectrometer is adapted for placement within a body near tissue to be characterized. The spectrometer includes a light source (3) and a plurality of light detectors (61). The light source generates light to illuminate the tissue. The detectors detect optical signals from the illuminated tissue and convert these optical signals to electrical signals. The miniaturized spectrometer can be disposed at the distal end of an interventional device (4). Optical conduits, such as fiber optic cables or strands, extending the length of the interventional device are not required when the miniature spectrometer is employed.</p>			

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

MINIATURE SPECTROMETER

Cross-Reference to Related Application

This is based on U.S. provisional patent application serial no. 60/033,334, filed November 21, 1996.

Technical Field

5 This invention relates to a spectrometer and, more particularly, to a miniature spectrometer for placement within a body for tissue characterization.

Background Information

10 Spectral analysis of living tissue can be used to detect various forms of cancer and other types of diseases. In spectral analysis, light illuminates tissue region under examination and a light detector detects optical properties of the illuminated tissue region by measuring light energy modified by its interaction with the tissue region in a pre-determined frequency and amplitude domain. Optical properties include absorption, luminescence, fluorescence, frequency and time-domain responses to various materials injected to the tissue region and other electromagnetic responses. Diseased tissue may be identified by comparing a spectrum obtained to spectra of
15 normal tissue obtained under the same controlled conditions.

 Current devices available for tissue characterization using spectral analysis include night vision sensing systems with filtering adapted to be used with endoscopes and multichannel fiber optic delivery systems. The latter systems typically include a light source, an optical conduit, a light applicator and receiver, a second light conduit, a spectrometer and a display unit. These
20 systems tend to be very expensive, to require large accompanying electronic systems, and to be complex requiring operator training.

 The optical fibers used as optical conduits in the multichannel fiber optic delivery systems are source of design difficulties. In order to transport an adequate amount of light energy from the light source to a tissue region inside a body, a significant amount of optical fibers must be
25 included in an interventional device. An interventional device, such as a catheter, however, does not include a lot of space and higher quality optical fibers, which take up less space, are expensive.

Optical fibers also lack mechanical properties necessary to be used with an interventional device. Optical fibers can break when flexed and have a relatively high stiffness compared to conventional catheter materials. Therefore, it is difficult to design a flexible tip for a catheter, which includes optical fibers and overall flexibility of an interventional device which include
5 optical fibers is limited.

Furthermore, optical fibers require an expensive terminating connector and must be properly coupled to afford adequate light throughput. Signal efficiency of fiber based devices depends greatly upon the devices' ability to couple sufficient light into the fibers at the desired wavelength. For spectral analysis, filtered broadband light sources are preferred over laser light
10 sources for cost and frequency versatility. However, it is a challenge to efficiently couple light from a lamp source into fibers with small diameters. Although laser light is more easily coupled into optical fibers, laser light sources are generally more expensive, are obtainable in only a few selected wavelengths, and are subject to more critical regulatory controls than other light sources. Furthermore, light emitted by the subject illuminated by a laser light tends to be weak and is also
15 subject to all of the loss mechanisms and inefficiencies problematical to a laser system.

Additional hardware, such as connectors and couplers, and the need to provide one or more optical conduits along the length of the interventional device, make conventional devices used for spectral analysis relatively expensive, inconvenient, and perhaps impractical.

Summary of the Invention

In one aspect, the invention features a miniature spectrometer for use in spectral analysis. The spectrometer includes a light source and a light detector for placement inside a body such that optical conduits are not necessary to deliver light signals to and from tissue inside the body.

5 The miniature spectrometer includes the light source and one or more light detectors. The light source illuminates a tissue region and the light detectors detect optical properties of the illuminated tissue by measuring modified light signals. The light detectors convert optical signals to electrical signals such that one or more electrical wires placed inside an interventional device can deliver the electrical signals from the tissue to a signal display or a microprocessor.

10 Embodiments of this aspect of the invention include the following features. The light source and the light detectors are energized by an external power supply through electrical wires. In another embodiment, an optically transparent tip encapsulates a spectrometer. The tip is shaped to optimize tissue contact and optical transmission. The tip encapsulating the spectrometer is disposed at a distal end of an interventional device. The tip may be coated with a
15 material to improve light transmission. The tip may include at least one fluid channel, which is in communication with a lumen inside the interventional device, to deliver a fluid to a tissue region. In one disclosed embodiment, a spectrometer of the invention includes a light source and the light detectors formed on a single substrate. The light source may be a light emitting diode and the light detectors may be a photodiode comprising multiple channels, where both devices are formed
20 on a silicon substrate. The light detector can include multiple channels to detect light emission at multiple wavelengths.

In another aspect, the invention features a method for characterizing tissue. According to the method, a spectrometer which includes a light source and a plurality of light detectors is provided. The spectrometer is placed inside a body near a tissue region to be characterized. The
25 light source and the detectors are connected to a power source through electrical wires. The energized light source generates light and illuminates the tissue region. The detectors measure light signals modified as a result of interacting with the tissue region. The light detectors convert received optical signals to electrical signals. In one embodiment of this aspect of the invention, an optically transparent tip encapsulates the spectrometer and is located near a distal end of an
30 interventional probe. The method can further include the step of rotating the spectrometer with respect to the tip. The rotation adjusts optical properties of the light transmitted to illuminate the tissue.

The foregoing and other objects, aspects, features, and advantages of the invention will become more apparent from the following description and from the claims.

Brief Description of the Drawings

In the drawings, like reference characters generally refer to the same parts throughout the different views. Also, the drawings are not necessarily to scale, emphasis instead generally being placed upon illustrating the principles of the invention.

5 FIG. 1A is a block diagram of a system for spectral analysis including a spectrometer module in communication with external components.

FIG. 1B shows a light detector of the spectrometer module of FIG. 1A in communication with an alternative electronic system for signal analysis.

10 FIG. 2A is a view in cross-section of a spectrometer module disposed at a distal end of an interventional device, the cross-section being along line 2A-2A of FIG. 2B.

FIG. 2B is a view in cross-section of the distal end of the spectrometer module of FIG. 2A.

FIG. 3 is a schematic diagram of an interventional device and a spectrometer module disposed at the distal end of the interventional device.

15 FIG. 4 is a view in cross-section of the spectrometer module of FIG. 2A encapsulated by a tip and disposed at the distal end of an interventional device.

FIG. 5 is a view in cross-section of a single substrate spectrometer module, the cross-section being along the length of the module.

Description

Referring to FIG. 1A, the spectrometer module 1 includes a light source 3 and a multichannel light detector 5 in close proximity to each other and to a region of interest 6. The region of interest 6 may be living tissue located inside a body. The light source 3 and the light detector 5 are located in close proximity to the region of interest so that they may both emit and/or couple the light energy efficiently with minimum intervening space or material. The light source 3 is in communication with a power supply or source 7 through a DC power line 9, and the light detector 5 is in communication with the power source 7 through a bias supply line 10. The power source 7 may provide direct current (DC) of either high or low voltage, alternating current (AC) of an appropriate frequency, or a pulse. AC power may be supplied to the light source 3 for the purpose of modulating the light source with a modulator 17. Alternatively, current with complex waveforms may be supplied to the light source 3. A diode may be placed in the circuit at the light source 3 to rectify some of the AC power so that it can be used to bias the detector 5. In the disclosed embodiment, a metering device 19 is placed at the source of power and employs a current sampler 20 in line to monitor and display the power applied to the light source 3. This configuration may be used to help calibrate the instrument during use.

One or more output lines 13 extend from the detector 5 to a microprocessor 25 and a display 11 through an amplifier 21 and an A-D converter 23. The output lines 13 may be shielded to reduce noise pickup. The output of the detector 5 is amplified through an amplifier 21 and sent to an analog-to-digital (A-D, A/D, or A-to-D) converter 23. The digitized signal can then be sent to a microprocessor 25 or other logical device for subsequent spectral analysis. An alternative signal processing system is shown in FIG. 1B.

Referring now to FIG. 1B, the alternative signal processing system includes a centering scale meter 33 driven by a DC source 34 placed in the common return line 38 extending from the light detector 38. This alternative signal processing system may be used to observe the different signal amplitudes of optical signals received by two or more channels of the light detector 5 operating simultaneously, or the normalized output of the light source versus the light energy received by the light detector 5. The amplitude of the reading may be used to determine the slope of the response signal relative to the input signal or to perform other more complex functions. It should be understood at this point that an equivalent operation may be obtained using a single channel light detector as long as a response property of the channel is varied over time. It may be possible to vary the response property by using, for example, one or more filters. In the case of a

single channel light detector, the two signals may be obtained sequentially, if desired. The functions provided by the above-described circuitry may be achieved with other or additional electrical, mechanical, and/or optical apparatus without departing from the spirit and scope of the invention.

5 Referring to FIGS. 2A and 2B, a spectrometer module 41 is disposed at a distal tip of an interventional device 4. The spectrometer module 41 is placed inside a housing 43. The housing 43 comprises an optically transparent material. The diameter of the housing 41 is small enough to allow the spectrometer module 41 and the housing 43 to pass through various lumens of catheters and body lumens such as vascular and nonvascular vessels. For example, the housing 43 for a
10 spectrometer module 41 used with a catheter 4 has a maximum diameter of about 0.25 inches. The housing 43 for a spectrometer module 41 used with a guidewire-sized device may have a maximum diameter of about 0.081 inches.

The spectrometer module 41 includes a light source 3, two light detectors 61, a lens 47, a
light amplifier 49, and a window 55. The light source 3 is a semiconductor diode source,
15 mounted such that the output end 45 is facing the distal end of the module 41, which is generally in line with the central axis of the interventional device 4. Alternatively, the light source 3 may be positioned such that the output end faces a direction transverse to the center axis of the interventional device 4. Light generated by the light source 3 may directly illuminate a tissue region or may be focused by a lens 47 before illuminating the tissue region. The lens 47 may be
20 shaped to focus the light into a desired pattern, or may be used to diffuse the light if needed. A frequency multiplier 49 is placed in the path of light generated by the light source 3 to amplify the frequency of the light output. The frequency multiplier 49 comprises an optically nonlinear substance. The optically nonlinear substance 49 is held in position with a ring holder 51, to maintain its position with respect to the position of the light source 3. Alternatively, the nonlinear
25 substance 49 may be bonded directly to the output end 45 of the light source 3 using an optically clear bonding material. The optically clear bonding material may be epoxy, cyanoacrylate, or sodium silicate. The bonding material may be placed directly upon the output end 45 of the light source 5 and its surrounding area, and the nonlinear substance 49 may be placed upon the bonding material. An example of an optically nonlinear substance suitable for use with a
30 spectrometer module of the invention is a potassium dihydrogen phosphate (KH_2PO_4) or KDP crystal. In order to improve light transmission, at least one surface of the KDP crystal may be coated with a fluoride layer that acts as a one-quarter wave matching layer 53. A window 55 is

placed at the distal end of the spectrometer module 41 to protect the module. The window 55 may be held in place by bonding the window 55 to the distal tip of the interventional device with an adhesive 57. In a preferred embodiment, the window 55 includes a bandstop filter characteristic that attenuates output frequencies of the light generated by the light source 3 while
5 permitting passage of light output having a predetermined frequency. Light output permitted to pass through the filter is often in the ultraviolet range, and particularly has wavelengths from about 300 nm to about 400 nm. Such filters are generally available and known. Examples of these types of filters include tinted glass, sandwiched dyes, and interference filters otherwise known as dichroic filters. Alternatively, variable filtration may be employed by rotating the inner
10 portion of the module 41 relative to portions of another colored material, such as a tinted plastic catheter sheath or a tip 81 shown in FIG. 4. The catheter sheath or the tip 81 may have differing filter characteristics owing to changes in thickness, or due to localized dyes.

One or more light detectors 61 and filters 63 may be disposed around the nonlinear substance 49 (FIG. 2B). The light detectors 61 may be, for example, silicon photodiodes,
15 cadmium sulfide slabs with electrodes, charge-coupled devices, or generally any light sensors that may be miniaturized and placed within the confines of a device smaller than about 0.250 inches or less in diameter. The light detectors 61 may be positioned at an angle (FIG. 2A) to aid in the collection of light emitted by the region of interest 6. Alternatively, the light detectors 61 may be disposed on a flat substrate adjacent to the lightsource 3. The light signals illuminating the region
20 of interest are modified as a result of interacting with the region of interest 6. The light detectors 61 detect the modified light signals. The light detectors 61 may also monitor light emission from the light source. The light detectors 61 are energized with the energy from the power supply 7 through a power line 10 (FIG. 1A). Frequency selective detectors 61 are produced by disposing filters 63 on the light detectors 61. The filters 63 attenuate one or more frequency bands of
25 energy received by the light detectors 61. Filters 63, for example, may be of the bandpass type admitting wavelengths selectively. A specific bandpass of one filter may be centered around 380 nm, while another filter may be centered around 440 nm. Signal wires 13 delivering signal output may be in the form of twisted pairs of wires or may share a common ground path. The signal wires 13 are threaded through one or more lumens 65 of the interventional device 4, and extend
30 back to a suitable connector located on or near the proximal end of the interventional device 4.

Referring to FIG. 3, the spectrometer module 41 of FIG. 2 is disposed at the distal end of an interventional device 70. In the disclosed embodiment, the module 41 is attached to the distal

end of a shaft 71, and the shaft 71 houses signal wires 9, 10, and 13. The shaft 71 terminates with a small connector 73 at the proximal end. The connector 73 may have one or more contacts arranged to permit electrical, optical, and mechanical connection to a mating connector. The shaft 71 also has a slidable stop 75 that may be prepositioned to allow control of the depth of placement within the body. The stop may be a collar with a collet ring 77 that tightens when twisted to provide a positive stop. The shaft 71 may comprise a tube, such as stainless steel hypo tube, superelastic (nitinol) tube, or the like. The advantage of such shafts is that they are relatively rigid and allow insertion into partly occluded passages. Very small shafts may be made with metal tubes. Shafts having outside diameters of about 0.005 inches may be provided, although in most instances, larger shafts with diameters of about 0.08 inches or larger are adequate. Lengths of the shafts may also vary between a few millimeters to over 200 centimeters. The shaft 71 may be made of a more flexible material if desired. Multi-layered counterwound wires of small diameter may be used as the shaft material. These shafts have relatively high lateral flexibility and good torsional stiffness, and can be positioned to specific angles by manual twisting or by a motor. Other shafts may be comprise plastics such as polyethylene, polyimide, or nylon and may have one or more lumens. Lumens carry electrical, optical or mechanical transmission lines, or cooling fluids. In the disclosed embodiment, the shaft 71 has a screw thread 79 at the distal end to facilitate attachment and detachment of the module 41 to the shaft 71. One possible use of the attachment thread may be to release the module 41 from the end of the shaft 71, once the module 41 is positioned inside a body, by unscrewing and releasing the module 41. The tubular shaft 71 may then slide over the small connector 73, which may be left outside the body. The module 41 may be re-connected to the shaft 71 before withdrawing the module 41 from the body.

Referring to FIG. 4, the spectrometer module 41 of FIG. 2A is located inside an optically transparent tip 81, and the tip 81 and the module 41 are disposed at the distal end of an interventional device 80. The tip 81 may comprise a plastic such as polystyrene, a glass such as quartz, or alternatively be molded out of a dissolvable material such as sucrose. The tip 81 includes a fluid channel 82 that is in communication with the central lumen 84 of the catheter body 83. The fluid channel 82 may be used to provide a coupling fluid such as water at or near the tip of the device, or to inject a dye (such as india ink) or a drug (such as Photofrin), or to collect a sample of fluid or tissue. The tip 81 may include secondary filters 87. Positioning the module 41 relative to the tip 81 allows variations in the optical pathway to be obtained. For

instance, the module 41 may be rotated within the tip 81, such that secondary filters line up with one or more of the detectors 61 or light emitted from the light source 3.

A catheter body 83 may house the module 41, by passing the module through the central lumen 84 of the catheter 83, to guide the module 41 to the region of interest in mucosal tissue 85.

5 The embodiment shown in Figure 4 allows the operator to monitor a change in the tissue as a result of a drug injections, or the selective uptake of a fluorescent dye. The shape of the tip 81 aids in the avoidance of specular reflections of light from the surface of the mucosal lining 85 and the displacement of intervening materials such as bacteria which often strongly fluoresce. The tip 81 can essentially provide angle independence, while avoiding the need for actual removal of
10 tissue material. If the tip 81 is slightly rounded, displacement of tissue is accomplished without actually shearing the tissue significantly. Penetration depth may be controlled by placing the shoulder 86 of the catheter 83 against the tissue and sliding the tip 81 relative to the catheter 83. Ranges of extension from flush or negative clearance to about 1.0 mm or greater protrusion of the tip 81 beyond the shoulder 86 are practical using a friction fit between the two components. The
15 shaft 71 (FIG. 3) and the module 41 may be bonded to the tip 81 if desired with clear epoxy. The advantage of such configuration is that the entire assembly may be slidably and rotatively positioned within catheter 83. The tubular form of catheter 83 is merely exemplary. Numerous catheter sheaths and other interventional devices that are used to conduct fluids may be used including needles, guidewires, guiding catheters, trocars, introducers, endoscopes, and stents.

20 The tube or the housing may be filled with an optically transparent material or a diffusing material. Examples of optically transparent material include epoxy, water, and oil. Examples of diffusing material include particulate matter suspended in a viscous fluid, like an epoxy which may harden or an elastomeric material which may remain flexible to conform to various anatomical conditions or be shaped into various catheter tips.

25 The interventional device of FIG. 4 may be made more useful, less expensive, and smaller by incorporating all of the functional elements into a single substrate which may be embedded, attached, disposed or implanted in interventional devices and living tissue at will. In FIG. 5, a single substrate spectrum analysis package 90 employs these features in such a compact arrangement. In the disclosed embodiment, the elements are formed on a doped, layered silicon
30 substrate. Alternatively, the substrate 91 may be an etched printed circuit on an epoxy fiberglass resin substrate. The light emitting portion is an integral light emitting diode arrangement 93 including etched semiconductor N material 95 and a diamond heat sink 97 bonded to one side of

the substrate 91. The gap 99 etched below the reference surface of the substrate 91 allows light energy to be directed to the mirror 101, which is bonded to the piezoelectric light modulator 103. The mirror 101 may be constructed by aluminizing a portion of the piezoelectric light modulator 103 after beveling and polishing the modulator 103. Alternatively, the mirror may include a small slab of glass material, about 0.150 mm square and 0.010 mm thick, bonded with a thin layer of epoxy resin to stack actuator in a position that allows clearance within the gap 99. The construction of the piezoelectric light modulator 103 may be accomplished by bonding a single layer of Lead Zirconate-Titanate (PZT) directly to the substrate 91 using a conductive epoxy and ultrasonically welding or epoxy bonding an electrode 105 with a fine copper wire 107, which is in turn bonded to an electrical terminal post 109. The terminal posts 109 can be about 0.030 mm in diameter and about 0.328 mm in length, and they can comprise brass wires plated with gold. A large post 110 is welded ultrasonically to the base of substrate 91 and serves as an orientation key, a mechanical stabilizer, and is also capable of carrying somewhat higher current.

Also etched from the substrate 91 is an avalanche photodiode (APD) array 121, which serves as a very sensitive light detector. In the embodiment shown in Figure 5, the light detector 121 has a two channel version. More channels, however, may be added by simply repeating the structure as follows: deposit Silicon oxide (SiO_2) layers 123 on N material layers 125, which are individually connected to posts 109 through fine wires 107. The depletion layer 127 is sandwiched between the N material layers 125 and the substrate 91, and may also serve as part of the common return circuit to post 110. A colored light filter 131 may be positioned over one or more of the light sensitive portions of the APD such that the spectral response of one channel is different from that of the other. In the disclosed embodiment, a colored light filter 131 is positioned over one channel. The filter, for example, may comprise a wave filter such as a dichroic filter made of a glass, a grating, or a dye. The filter 131 may be temporarily positioned over a silicon oxide layer 123 and held in place while optical potting plastic 133 is molded over the assembly. Materials such as polystyrene, polycarbonate and methyl-methacrylate, for example, may be used as the optical potting plastic to cast or injection mold a desired shape of the package 90. Other materials such as urethanes may be used to form the cast as long as they are sufficiently transmissive of light energy and are reasonably elastic to allow small excursion such as the mirror 101. An air space around the gap 99 may be desirable depending on the index of refraction needed in the vicinity of the mirror 101 and the output end of the light emitting diode 93. One way to accomplish this is to place a premolded frame over the gap 99, which prevents

the flow of potting material into that area. The frame may be injection molded out of the material also being used for the package 90 or a material that has a higher melting temperature. The frame may be bonded in place with a thin layer of clear epoxy film. The package 90 may be shaped to permit modification of the optical signals, which may enter or exit the package. In the

5 embodiment shown, the serrated lens 135 is molded or embossed into the surface of the package 90. The advantage of this configuration is that a polished mold may be used to form a precision optical surface as desired. The state of the art injection molding techniques and relatively low viscosity thermoplastics such as polystyrene allow creation of very fine features with controllable dimensions and step heights on the surface. A dimension of the surface feature may be in the

10 range of about 0.005 mm. Even finer features of less than 0.005 mm may be embossed using pressure and a photoetched master such that binary optical steps, holograms, or gratings capable of diffracting IR, visible, and UV light may be formed directly on the surface of the package 90. Creation of such features on the surface, or within the assembly, avoids the need for additional, expensive optical components and their holders. A conventional curved lens 137 is created on the

15 surface of the package 90 to focus the light energy as desired. The conventional curved lens 137 also may be molded to the surface during the molding operation. A grating may disperse light across the one or more detectors providing frequency selection capability.

Spectrometer modules according to the invention are designed to place the light source and the light detector in proximity to a tissue region under spectral analysis. Tissue

20 characterization using spectral analysis is based on the understanding that light emitted from a light source interacts with the tissue and modifies the light. Absorption, scattering, and other loss of energy occurs when light interacts with the tissue. Various tissue types, however, have differing absorption and reflection properties. Therefore, tissue can be characterized using spectral analysis. These interaction phenomena, however, also limit the depth of light penetration

25 that can be achieved. Therefore, energy loss due to extraneous factors may be severe when the light source is not located near the tissue of interest. The invention provides means for placing the light source and the light detector near the tissue of interest, such that efficient operation can be achieved. Therefore, the spectrometer module of the invention eliminates unnecessary light loss and allows the light detector to detect light modification caused by the interaction with the

30 tissue.

In general, any type of light detector capable of detecting modified light signals due to its interaction with the subject under analysis and capable of being made sufficiently small to fit in an

interventional device may be used in accordance with the invention. For example, a charge coupled device (CCD) sensor may be arranged circumferentially around the energy generating source and connected via signal wires. Alternatively, silicon photodiodes, cadmium sulfide cells or scintillation detectors may be arranged such that a returning portion of the lightwave energy is captured and measured. In the case of CCD type sensors, a large number of such devices may be incorporated in a very small area, although only one such sensor may be necessary to obtain and measure a useful signal. Alternatively, two or more sensors may be used in accordance with the invention. The advantage of using multiple sensors is that it eliminates the need for changing filters. Filter x for instance, may be arranged to admit blue lightwaves, while filter y may be arranged to admit red lightwaves, such that the relative intensity of two wavelengths can create a slope which may indicate a particular tissue type or state.

Any light source capable of being placed in an interventional device may be used according to the invention. An ordinary incandescent light source such as a tungsten filament light source with appropriate filtering disposed thereon, an arc lamp, a mercury vapor lamp, a xenon flash lamp, gas discharge tubes filled with various gases, metallic vapors, an acoustically driven sonoluminescent source capable of generating visible and UV light, and X-rays, a Gunn diode source of super high frequency energy (SHF), light-emitting diodes, and other light sources capable of either long or short duration output, at long or short wavelengths may be used with the invention.

Possible light source systems and light detection arrangements are described in two commonly-owned U.S. provisional patent applications, namely U.S. provisional patent application serial no. 60/033,333 and U.S. provisional patent application serial no. 60/033,335. These disclosures, and any regular U.S. patent applications converted on the basis of one or both of these provisional applications, are hereby incorporated herein by reference. In general, a light source system and a light detection system are selected for use according to the invention based on various factors including, for example, cost, complexity, miniaturization, and therapeutic properties.

The shape of the spectrometer module of the invention may be any form suitable for optimizing the contact between the module and the region of interest or optical transmission of generated light to the region of interest. Possible shapes include, for example, concave, stepped, cylindrical, chisel tipped, conical, convex, and hemispherical. In addition, the outer or inner

surface of the module may be coated with a special material to enhance the light transmitting properties or be provided with a microlens, a binary optical step, or a wavelength filter.

Although the invention has been described in terms of both the light source system and the light detector system, it should be understood by those skilled in the art that the light source
5 system alone and the detector system alone may be used in certain circumstances where the need arises. Furthermore, it should be understood that either the light source or the detector may be substituted with a non-light generating or receiving device. Examples include radiofrequency generating and receiving systems capable of spectroscopy at longer wavelengths, and x-ray
10 generating and receiving systems capable of x-ray spectroscopy. In general, some of the basic features of the invention include generating a local energy source, applying the energy source to a selected area of tissue, and collecting energy which has been modified by interaction with the selected area of tissue. The collected energy signals preferably are analyzed to characterize the tissue, and the results indicated to an operator or user.

Variations, modifications, and other implementations of what is described herein will
15 occur to those of ordinary skill in the art without departing from the spirit and the scope of the invention as claimed. Accordingly, the invention is to be defined not by the preceding illustrative description but instead by the spirit and scope of the following claims.

What is claimed is:

Claims

- 1 1. A spectrometer, comprising:
2 a light source for illuminating tissue; and
3 a plurality of light detectors for detecting optical properties of the illuminated tissue, the
4 plurality of light detectors adapted for converting optical signals to electrical signals, the light
5 source and the plurality of light detectors adapted for placement together within a body.
- 1 2. The spectrometer of claim 1 further comprising a lens disposed in a pathway of light
2 generated by the light source for focusing or diffusing the light.
- 1 3. The spectrometer of claim 1 further comprising a frequency multiplier disposed in a
2 pathway of light generated by the light source for amplifying frequency of the light emission.
- 1 4. The spectrometer of claim 1 further comprising a filter disposed in a pathway of light
2 generated by the light source for illuminating tissue with light having a predetermined wavelength.
- 1 5. The spectrometer of claim 1 wherein the light source and the plurality of light detectors
2 are sized to provide a miniature spectrometer, wherein a dimension of the spectrometer in any
3 direction is less than about 3 mm.
- 1 6. The spectrometer of claim 1 wherein the plurality of light detectors detect light
2 emission at multiple wavelengths.
- 1 7. The spectrometer of claim 1 wherein at least one detector of the plurality of light
2 detectors is adapted for monitoring light emission from the light source.
- 1 8. The spectrometer of claim 1 further comprising at least one filter disposed adjacent a
2 detector of the plurality of light detectors for selectively detecting light emission having a pre-
3 determined wavelength.
- 1 9. The spectrometer of claim 1 wherein the light source and the plurality of light detectors
2 are formed on a single substrate.
- 1 10. The spectrometer of claim 9 wherein the light source is a light emitting diode and the
2 plurality of light detectors is a photodiode comprising a plurality of channels.
- 1 11. The spectrometer of claim 1 further comprising a housing encapsulating the light
2 source and the plurality of light detectors.
- 1 12. The spectrometer of claim 11 wherein the housing is substantially transparent.

1 13. The spectrometer of claim 11 wherein the housing is adapted for directing or diffusing
2 light generated by the light source.

1 14. The spectrometer of claim 1 further comprising an interventional device adapted to
2 place the light source and the plurality of light detectors within a body.

1 15. The spectrometer of claim 14 wherein the light source and the plurality of light
2 detectors are encapsulated in a housing and the housing is adapted for attachment to a distal end
3 of the interventional device.

1 16. The spectrometer of claim 14 wherein the interventional device is selected from a
2 group consisting of catheter, guidewire, needle, endoscope, implant, and trocar.

1 17. The spectrometer of claim 14 further comprising an optically transparent tip
2 encapsulating the light source and the plurality of detectors disposed at a distal end of the
3 interventional device, wherein the tip is shaped for optimizing tissue contact and optical
4 transmission.

1 18. The spectrometer of claim 14 wherein the light source and the plurality of light
2 detectors are disposed inside the interventional device.

1 19. The spectrometer of claim 17 wherein a surface of the tip is coated with a material for
2 improving light transmission.

1 20. The spectrometer of claim 17 wherein the tip comprises at least one fluid channel in
2 communication with a lumen in the interventional device for delivering a fluid necessary for a
3 monitoring procedure.

1 21. The spectrometer of claim 17 wherein the tip comprises at least one filter and the light
2 source is adapted to be rotated with respect to the tip, thereby adjusting an optical property of the
3 light generated by the light source.

1 22. The spectrometer of claim 1 further comprising an external power source in electrical
2 communication with the light source and the plurality of light detectors.

1 23. A spectrometer module comprising a plurality of light detectors for detecting optical
2 properties of tissue, wherein each detector comprises multiple channels for detecting light
3 emission having multiple wavelengths, is capable of converting optical signals to electrical signals,
4 and is sufficiently small to allow the module to be placed within a body.

- 1 24. A method for characterizing tissue comprising:
2 providing a spectrometer comprising a light source and a plurality of light detectors
3 adapted for converting optical signals to electrical signals;
4 placing the spectrometer inside a body near tissue to be characterized;
5 connecting the light source and the plurality of light detectors to a power source;
6 illuminating the tissue; and
7 measuring optical properties of the illuminated tissue.
- 1 25. The method of claim 24 further comprising monitoring light emission from the light
2 source.
- 1 26. The method of claim 24 wherein providing a spectrometer comprises providing a
2 module having the light source and the plurality of light detectors formed on a single substrate.
- 1 27. The method of claim 24 further comprising providing an interventional device,
2 disposing the spectrometer near a distal end of the interventional device and inserting the
3 interventional device inside the body.
- 1 28. The method of claim 26 wherein the spectrometer is encapsulated by an optically
2 transparent tip disposed near the distal end of the interventional device and further comprising
3 rotating the module with respect to the tip, thereby adjusting optical property of the light
4 generated by the light source.
- 1 29. The method of claim 26 wherein the spectrometer is encapsulated by an optically
2 transparent tip comprising at least one fluid channel in communication with a lumen in the probe
3 and delivering a fluid necessary for a monitoring procedure to the illuminated tissue.
- 1 30. The method of claim 24 wherein the plurality of light detectors comprises a light
2 detector having a plurality of channels and measuring optical properties comprises detecting light
3 emission at multiple wavelengths.
- 1 31. The method of claim 24 wherein illuminating the tissue comprises generating light
2 from the light source and focusing the generated light on the tissue to be illuminated with a lens
3 disposed in a pathway of the generated light.
- 1 32. The method of claim 24 wherein illuminating the tissue comprises generating light
2 from the light source and diffusing the generated light with a lens disposed in a pathway of the
3 generated light to illuminate the tissue.

1 33. The method of claim 24 wherein illuminating the tissue comprises generating light
2 from the light source, amplifying the generated light by passing the light through an optically
3 nonlinear substance disposed in a pathway of the generated light and illuminating the tissue with
4 the light.

1 34. A method for characterizing tissue comprising:
2 placing a spectrometer comprising a plurality of light detectors inside a body near tissue to
3 be characterized, wherein the at least one light detector converts optical signals to electrical
4 signals;
5 connecting the plurality of light detectors to a power source;
6 illuminating the tissue; and
7 measuring optical properties of the illuminated tissue.

1 35. A spectrometer, comprising:
2 a source of ultraviolet (UV) light for illuminating tissue; and
3 at least one light detector for detecting UV light emissions from the illuminated tissue, the
4 at least one light detector adapted for converting UV light emissions into electrical signals, the
5 light source and the at least one light detector adapted for placement together within a body.

1 36. The spectrometer of claim 35 further comprising at least one filter disposed adjacent
2 the at least one detector for selectively detecting UV light emission within a predetermined
3 wavelength band.

1 37. The spectrometer of claim 36 wherein the at least one filter is a bandpass filter with a
2 passband centered at a wavelength of 380 nm.

1 38. The spectrometer of claim 36 wherein the at least one filter is a bandpass filter with a
2 passband centered at a wavelength of 440 nm.

1/3




FIG. 1A




FIG. 1B

RECTIFIED SHEET (RULE 91)
ISA/EP

2/3




FIG. 2A




FIG. 2B




FIG. 3

RECTIFIED SHEET (RULE 91)
ISA/EP

3/3




FIG. 4




FIG. 5
RECTIFIED SHEET (RULE 91)
ISA/EP

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 97/20324

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 G01N21/25 G01N21/33 A61B5/00

According to International Patent Classification(IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G01N A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 350 375 A (DECKELBAUM LAWRENCE I ET AL) 27 September 1994 see column 4, line 47 - line 68; figure 1 ---	1, 3, 6-8, 22-25, 30-38
X	EP 0 314 937 A (SIEMENS ELEMA AB ;SIEMENS AG (DE)) 10 May 1989	1, 2, 4, 6-9, 11-18, 22-27, 30, 34
A	see page 2, line 44 - line 45 see page 9, line 10 - line 25; figure 12 --- -/--	5, 10

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "Δ" document member of the same patent family

Date of the actual completion of the international search

2 March 1998

Date of mailing of the international search report

11/03/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Scheu, M

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 97/20324

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 127 407 A (TAN JOSEF K S) 7 July 1992	1, 2, 4, 6-8, 10-18, 22-27, 30
A	see column 2, line 20 - line 59 see column 3, line 9 - line 11 see figures 1-3, 8 -----	5, 10
A	WO 91 15151 A (NELLCOR INC) 17 October 1991 see figure 1B -----	2, 31, 32

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 97/20324

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5350375 A	27-09-94	NONE	
EP 0314937 A	10-05-89	AU 2355288 A	13-04-89
		DE 3854781 D	25-01-96
		DE 3854781 T	02-05-96
		JP 1212539 A	25-08-89
		US 4815469 A	28-03-89
US 5127407 A	07-07-92	US 5024226 A	18-06-91
		AT 134849 T	15-03-96
		AT 148323 T	15-02-97
		CA 2023355 A	18-02-91
		DE 69025673 D	11-04-96
		DE 69025673 T	01-08-96
		DE 69029869 D	13-03-97
		DE 69029869 T	05-06-97
		EP 0413588 A	20-02-91
		EP 0651968 A	10-05-95
		ES 2084662 T	16-05-96
		ES 2097063 T	16-03-97
		GR 1001029 B	31-03-93
		JP 3228746 A	09-10-91
WO 9115151 A	17-10-91	US 5099842 A	31-03-92
		AU 638577 B	01-07-93
		AU 7751791 A	30-10-91
		CA 2054688 A	05-10-91
		DE 69110812 D	03-08-95
		DE 69110812 T	14-03-96
		EP 0477355 A	01-04-92
		JP 8015487 B	21-02-96
		JP 4506316 T	05-11-92